


WP 09T/WS

Order No.: 2700309



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2700309>

Web panel with 9.0" graphics-capable TFT widescreen display, 800 x 480 pixels, 1 x Ethernet, 2 x USB, and integrated micro browser

Commercial data	
GTIN (EAN)	
sales group	K310
Pack	1 pcs.
Customs tariff	85371099
Catalog page information	Page 307 (NTK-2010)

Product notes

WEEE/RoHS-compliant since: 11/19/2009



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Display data	
Display	22.9 cm/9" TFT active
Resolution	800 x 480 Pixel (WVGA)
Brightness	CCFL
Half-life of background illumination	50000 h
Touch screen	Resistive industrial touch screen

Colors	65,536 colors
--------	---------------

Computer data

Processor	RISC ARM9 CPU; 200 MHz
Main memory	32 MByte SDRAM
Data memory	16 MB Flash
Interfaces	10/100 MBit Ethernet; 2 x USB Host 2.0
Operating systems	Windows CE 6.0

General data

External dimension, width	260 mm
External dimension, height	172 mm
External dimension, depth	5 mm
Note regarding external dimension	Dimensions of the front plate
Installation dimension, width	252 mm
Installation dimension, height	164 mm
Mounting type	Installation in front plate
Weight	1300 g

Ambient Conditions

Degree of protection	IP65 (front), IP20 (back)
Ambient temperature (operation)	0 °C ... 50 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C
Permissible humidity (operation)	20 % ... 85 % (no condensation)
Permissible humidity (storage/transport)	10 % ... 95 % (no condensation)
Vibration (operation)	DIN EN 60068-2-6
Shock	DIN EN 60068-2-27

Certificates / Approvals

Certification

GL

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact
Technical modifications reserved;