

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△	3	RE-E-08257	K.H	A-5	61.12.2/	△			
△					△				
APPLICABLE STANDARD		TIA/EIA-568-B.2 CATEGORY5e △							
RATING	OPERATING TEMPERATURE RANGE	-25 °C TO 60 °C			STORAGE TEMPERATURE RANGE	-25 °C TO 60 °C			
	VOLTAGE	125 V AC			CURRENT	1 A △			
SPECIFICATIONS									
ITEM		TEST METHOD			REQUIREMENTS			QT	AT
CONSTRUCTION									
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING.			○	○
MARKING		CONFIRMED VISUALLY.						○	○
ELECTRIC CHARACTERISTICS									
CONTACT RESISTANCE		100 mA (DC OR 1000 Hz AC). MEASUREMENT POINTS SHALL BE AS FOLLOWS			230 mΩ MAX.			○	○
		<p>(ONE EXAMPLE OF CONNECTOR CONFIGURATION IS SHOWN.)</p>							
INSULATION RESISTANCE		100 V DC.			100 MΩ MIN.			○	○
VOLTAGE PROOF		500 V AC FOR 1 min.			NO FLASHOVER OR BREAKDOWN.			○	○
NEAR END CROSSTALK(NEXT)LOSS		MEASURED MINIMUM NEXT LOSS FOR EACH PAIR COMBINATION AT 100 Hz			43 dB MIN. △			○	-
MECHANICAL CHARACTERISTICS									
MECHANICAL OPERATION		200 TIMES INSERTIONS AND EXTRACTIONS.			① CONTACT RESISTANCE: 250 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.			○	-
VIBRATION		FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, — m/s ² AT 2 h, FOR 3 DIRECTIONS.			① NO ELECTRICAL DISCONTINUITY OF 5 μs. ② CONTACT RESISTANCE: 250 mΩ MAX.			○	-
SHOCK		490 m/s ² DIRECTIONS OF PULSE 11 ms AT 3 TIME FOR 3 DIRECTION.			③ NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.			○	-
ENVIRONMENTAL CHARACTERISTICS									
DAMP HEAT (STEADY STATE)		EXPOSED AT 40 °C, 90 TO 95 %, 500 h.			① CONTACT RESISTANCE: 250 mΩ MAX. ② INSULATION RESISTANCE: 1 MΩ MIN. (AT HIGH HUMIDITY) ③ INSULATION RESISTANCE: 10 MΩ MIN. (AT DRY) ④ NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.			○	-
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -55±3 →5 TO 35→85±2 →5 TO 35°C TIME 30 TO 35→5 MAX→30 TO 35 →5 MAX min UNDER 5 CYCLES.			① CONTACT RESISTANCE: 250 mΩ MAX. ② INSULATION RESISTANCE: 100 MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.			○	-
CORROSION SALT MIST		EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.			① CONTACT RESISTANCE: 250 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.			○	-
REMARKS				DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED	
				S.Sato 00.07.03	S.Sato 00.07.03	T.Watanabe 00.07.03	H.Miwa 00.07.03		
Unless otherwise specified, refer to JIS C 5402.									
Note QT:Qualification Test AT:Assurance Test ○:Applicable Test									
HRS HIROSE ELECTRIC CO., LTD.				SPECIFICATION SHEET			PART NO. TM21P - 88P 「 」		
CODE NO.(OLD)		DRAWING NO. ELC4 - 121484 - 04		CODE NO. CL 222 - 2862 - 9 - 「 」				1 1	

TO
Q2

