

Specification Sheet

Part Number: WSM60IMHSUVH1



Weld Stud Mount, Max Bundle Diameter 6.0", Stud Diameter .24", PA66HIRHSUV, Black, 500/pkg

Article Number	151-00146
Type	WSM60
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none">•Design makes installation along frame rails fast and easy.•Using weld stud eliminates the need for grinding down painted surfaces which saves time.•Weld Stud eliminates need for stocking multiple sized metal P-Clamps which saves time and cost.
Quantity Per	bag

Product Description

When used in conjunction with a cable tie, the Weld Stud Mount significantly reduces time and labor, and eliminates the need for multiple sized P-clamps, nuts, and bolts. Simply weld the stud to the surface of any painted frame rail, and begin bundling with HellermannTyton cable ties. This eliminates the need in having to grind the surface in preparation. Adjusts to a wide variety of bundle diameters when used with HellermannTyton heavy duty T120, T250, T255 and Wide Strap Cable Ties.

Short Description

Weld Stud Mount, Max Bundle Diameter 6.0", Stud Diameter .24", PA66HIRHSUV, Black, 500/pkg

Global Part Name

WSM60-PA66HIRHSUV-BK

Length L (Imperial)

1.32

Length L (Metric)

33.5

Width W (Imperial)

1.07

Width W (Metric)

27.2

Bundle Diameter Max (Imperial)

6.0

Bundle Diameter Max (Metric)

152.4

Height H (Imperial)

1.06

Height H (Metric)

27.0

Stud Diameter (Metric)

6.0 mm

Stud Diameter (Imperial)

0.24

Material

Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

Material Shortcut

PA66HIRHSUV

Flammability

UL 94 HB

Operating Temperature (Metric)

-40°F to +230°F (-40°C to +110°C)

Reach Complaint(Article 33)

Yes

ROHS Complaint

Yes

Package Quantity(Imperial)

500

Package Quantity (Metric)

500

Customs Number

3926909987

Content Unit(BMEcat)

pcs.